

Teknisk informasjon RBES

Temperatur i skap/counter 2-4 C.

Modell Model	Artikkelnummer Item number	Mål Dimension	Vekt netto/brutto Weight net/gros	Transport volum Transport volume
RBES-1200	07531200	1202 x 650 x 900/1420 mm	179 / 193 kg	1,72 m ³
RBES-1200 S	07531200	1202 x 650 x 900/1420 mm	159 / 173 kg	1,72 m ³
RBES-1600	07531600	1602 x 650 x 900/1420 mm	204 / 220 kg	2,05 m ³
RBES-1600 S	07531600	1602 x 650 x 900/1420 mm	184 / 200 kg	2,05 m ³
RBES-2000	07532000	2002 x 650 x 900/1420 mm	207 / 227 kg	2,40 m ³
RBES-2000 S	07532000	2002 x 650 x 900/1420 mm	187 / 207 kg	2,40 m ³
RBES-2400	07532400	2402 x 650 x 900/1420 mm	270 / 285 kg	2,75 m ³
RBES-2400 S	07532400	2402 x 650 x 900/1420 mm	250 / 265 kg	2,75 m ³

S= sentralkjøling / central cooling.

Modell Model	Dører Doors	Kapasitet i underdel Capacity in counter	Kapasitet i brønn Capacity in well
RBES-1200	2	10 x 1/1 GN	3 x 1/1 GN – 150 mm
RBES-1200 S	2	10 x 1/1 GN	3 x 1/1 GN – 150 mm
RBES-1600	3	15 x 1/1 GN	4 x 1/1 GN – 150 mm
RBES-1600 S	3	15 x 1/1 GN	4 x 1/1 GN – 150 mm
RBES-2000	4	20 x 1/1 GN	5 x 1/1 GN – 150 mm
RBES-2000 S	4	20 x 1/1 GN	5 x 1/1 GN – 150 mm
RBES-2400	5	25 x 1/1 GN	7 x 1/1 GN – 150 mm
RBES-2400 S	5	25 x 1/1 GN	7 x 1/1 GN – 150 mm

Modell Model	Strømart Kind of current	Kjøleeffektbehov ved sentralkjøling Power requirement central cooling
RBES-1200	230 V - 1 – 50 HZ – 480 W	
RBES-1200 S	230 V - 1 – 50 HZ – 150 W	400 W /-10
RBES-1600	230 V - 1 – 50 HZ – 480 W	
RBES-1600 S	230 V - 1 – 50 HZ – 150 W	400 W /-10
RBES-2000	230 V - 1 – 50 HZ – 520 W	
RBES-2000 S	230 V - 1 – 50 HZ – 150 W	550 W /-10
RBES-2400	230 V - 1 – 50 HZ – 520 W	
RBES-2400 S	230 V - 1 – 50 HZ – 150 W	550 W /-10

TD-500711 - Rev. 23. nov. 2015 -GS.

Tegninger og øvrig dokumentasjon finnes på våre nettsider www.rustfriebergh.no

Sertifisert av 