

# Teknisk informasjon RBE-GD

Temperatur i skap/counter 2-4 C.

Modell Model	Artikkelnummer Item number	Mål Dimension	Vekt netto/brutto Weight net/gros	Transport volum Transport volume
RBE-1200-GD	07111200	1202 x 1400 x 900 mm	140 / 163 kg	2,00 m <sup>3</sup>
RBE-1200-GD S	07111200	1202 x 1400 x 900 mm	120 / 153 kg	2,00 m <sup>3</sup>
RBE-1600-GD	07111600	1602 x 1400 x 900 mm	183 / 196 kg	2,60 m <sup>3</sup>
RBE-1600-GD S	07111600	1602 x 1400 x 900 mm	163 / 176 kg	2,60 m <sup>3</sup>
RBE-2000-GD	07112000	2002 x 1400 x 900 mm	227 / 242 kg	3,20 m <sup>3</sup>
RBE-2000-GD S	07112000	2002 x 1400 x 900 mm	207 / 222 kg	3,20 m <sup>3</sup>
RBE-2400-GD	07112400	2402 x 1400 x 900 mm	270 / 285 kg	3,80 m <sup>3</sup>
RBE-2400-GD S	07112400	2402 x 1400 x 900 mm	250 / 260 kg	3,80 m <sup>3</sup>

S= sentralkjøling / central cooling.

Modell Model	Dører Doors	Kapasitet i underdel Capacity in counter
RBE-1200-GD	4	20 x 1/1 GN
RBE-1200-GD S	4	20 x 1/1 GN
RBE-1600-GD	6	30 x 1/1 GN
RBE-1600-GD S	6	30 x 1/1 GN
RBE-2000-GD	8	40 x 1/1 GN
RBE-2000-GD S	8	40 x 1/1 GN
RBE-2400-GD	10	50 x 1/1 GN
RBE-2400-GD S	10	50 x 1/1 GN

Modell Model	Strømart Kind of current	Kjøleeffektbehov ved sentralkjøling Power requirement central cooling
RBE-1200-GD	230 V - 1 - 50 HZ - 520 W	
RBE-1200-GD S	230 V - 1 - 50 HZ - 150 W	520 W /-10
RBE-1600-GD	230 V - 1 - 50 HZ - 520 W	
RBE-1600-GD S	230 V - 1 - 50 HZ - 150 W	520 W /-10
RBE-2000-GD	230 V - 1 - 50 HZ - 520 W	
RBE-2000-GD S	230 V - 1 - 50 HZ - 150 W	620 W /-10
RBE-2400-GD	230 V - 1 - 50 HZ - 520 W	
RBE-2400-GD S	230 V - 1 - 50 HZ - 150 W	620 W /-10

TD-500712 - Rev. 18. des. 2015 -GS.

Tegninger og øvrig dokumentasjon finnes på våre nettsider [www.rustfriebergh.no](http://www.rustfriebergh.no)

Sertifisert av 