

Teknisk informasjon RBE-V

Temperatur i skap/counter 2-4 C.

Modell Model	Artikkelnummer Item number	Mål Dimension	Vekt netto/brutto Weight net/gros	Transport volum Transport volume
RBE-V-855	07340855	855 x 700 x 900 mm	117 / 130 kg	1,00 m ³
RBE-V-855 S	07340855	855 x 700 x 900 mm	97 / 110 kg	1,00 m ³
RBE-V-1255	07341255	1255 x 700 x 900 mm	159 / 173 kg	1,32 m ³
RBE-V-1255 S	07341255	1255 x 700 x 900 mm	139 / 153 kg	1,32 m ³
RBE-V-1655	07341655	1655 x 700 x 900 mm	184 / 200 kg	1,65 m ³
RBE-V-1655 S	07341655	1655 x 700 x 900 mm	164 / 180 kg	1,65 m ³
RBE-V-2055	07342055	2055 x 700 x 900 mm	187 / 207 kg	2,00 m ³
RBE-V-2055 S	07342055	2055 x 700 x 900 mm	167 / 187 kg	2,00 m ³
RBE-V-2455	07342455	2455 x 700 x 900 mm	250 / 265 kg	2,35 m ³
RBE-V-2455 S	07342455	2455 x 700 x 900 mm	230 / 245 kg	2,35 m ³

S= sentralkjøling / central cooling.

Modell Model	Dører Doors	Kapasitet i underdel Capacity in counter
RBE-V-855	1	5 x 1/1 GN
RBE-V-855 S	1	5 x 1/1 GN
RBE-V-1255	2	10 x 1/1 GN
RBE-V-1255 S	2	10 x 1/1 GN
RBE-V-1655	3	15 x 1/1 GN
RBE-V-1655 S	3	15 x 1/1 GN
RBE-V-2055	4	20 x 1/1 GN
RBE-V-2055 S	4	20 x 1/1 GN
RBE-V-2455	5	25 x 1/1 GN
RBE-V-2455 S	5	25 x 1/1 GN

Modell Model	Strømart Kind of current	Kjøleeffektbehov ved sentralkjøling Power requirement central cooling
RBE-V-855	230 V - 1 - 50 HZ - 480 W	
RBE-V-855 S	230 V - 1 - 50 HZ - 150 W	400 W /-10
RBE-V-1255	230 V - 1 - 50 HZ - 480 W	
RBE-V-1255 S	230 V - 1 - 50 HZ - 150 W	400 W /-10
RBE-V-1655	230 V - 1 - 50 HZ - 480 W	
RBE-V-1655 S	230 V - 1 - 50 HZ - 150 W	400 W /-10
RBE-V-2055	230 V - 1 - 50 HZ - 520 W	
RBE-V-2055 S	230 V - 1 - 50 HZ - 150 W	550 W /-10
RBE-V-2455	230 V - 1 - 50 HZ - 520 W	
RBE-V-2455 S	230 V - 1 - 50 HZ - 150 W	550 W /-10

TD-500714 - Rev. 23. nov. 2015 -GS.

Tegninger og øvrig dokumentasjon finnes på våre nettsider www.rustfriebergh.no

Sertifisert av 