

Teknisk informasjon KBKS-160

Temperatur i brønn/well 4-7 C.

Modell Model	Artikkelnummer Item number	Kapasitet i brønn Capacity in well	Vekt netto/brutto Weight net/gros	Transport volum Transport volume
KBKS-160-1 GN	07771000	1 x 1/1 GN-150 mm	57 / 72 kg	0,40 m ³
KBKS-160-1 GN S	07771000	1 x 1/1 GN-150 mm	37 / 57 kg	0,40 m ³
KBKS-160-2 GN	07732000	2 x 1/1 GN-150 mm	77 / 92 kg	0,66 m ³
KBKS-160-2 GN S	07732000	2 x 1/1 GN-150 mm	57 / 77 kg	0,66 m ³
KBKS-160-3 GN	07733000	3 x 1/1 GN-150 mm	89 / 104 kg	0,97 m ³
KBKS-160-3 GN S	07733000	3 x 1/1 GN-150 mm	69 / 84 kg	0,97 m ³
KBKS-160-4 GN	07734000	4 x 1/1 GN-150 mm	110 / 125 kg	1,22 m ³
KBKS-160-4 GN S	07734000	4 x 1/1 GN-150 mm	90 / 105 kg	1,22 m ³
KBKS-160-5 GN	07735000	5 x 1/1 GN-150 mm	132 / 144 kg	1,47 m ³
KBKS-160-5 GN S	07735000	5 x 1/1 GN-150 mm	112 / 124 kg	1,47 m ³
KBKS-160-6 GN	07736000	6 x 1/1 GN-150 mm	155 / 170 kg	1,75 m ³
KBKS-160-6 GN S	07736000	6 x 1/1 GN-150 mm	135 / 150 kg	1,75 m ³

S= sentralkjøling / central cooling.

Modell Model	Mål Dimension	Avløp Drain	Strømart Kind of current
KBKS-160-1 GN	400 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 145 W
KBKS-160-1 GN S	400 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 35 W
KBKS-160-2 GN	800 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 145 W
KBKS-160-2 GN S	800 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 35 W
KBKS-160-3 GN	1200 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 145 W
KBKS-160-3 GN S	1200 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 35 W
KBKS-160-4 GN	1525 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 200 W
KBKS-160-4 GN S	1525 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 35 W
KBKS-160-5 GN	1850 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 255 W
KBKS-160-5 GN S	1850 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 35 W
KBKS-160-6 GN	2175 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 255 W
KBKS-160-6 GN S	2175 x 650 x 900 mm	3/4" – DN 20	230 V - 1 – 50 HZ – 35 W

Modell Model	Kjølemedie Refrigerant	Kapillarrør	Kjøleeffektbehov ved sentralkjøling Power requirement central cooling
KBKS-160-1 GN	R290 – 0,062 kg	Ø 0,8 – 1500 mm	
KBKS-160-1 GN S			250 W /-10
KBKS-160-2 GN	R290 – 0,090 kg	Ø 1,0 – 3000 mm	
KBKS-160-2 GN S			250 W /-10
KBKS-160-3 GN	R290 – 0,110 kg	Ø 1,0 – 3000 mm	
KBKS-160-3 GN S			250 W /-10
KBKS-160-4 GN	R290 – 0,130 kg	Ø 1,0 – 1600 mm	
KBKS-160-4 GN S			350 W /-10
KBKS-160-5 GN	R290 – 0,150 kg	Ø 0,8 – 2000 mm	
KBKS-160-5 GN S			470 W /-10
KBKS-160-6 GN	R290 – 0,150 kg	Ø 0,8 – 1290 mm	
KBKS-160-6 GN S			470 W /-10

TD-500740 - Rev. 1. mars. 2023 -GS.

Tegninger og øvrig dokumentasjon finnes på våre nettsider www.rustfriebergh.no