

Teknisk informasjon KBKNS-160

Temperatur i brønn/well 4-7 C.

Modell Model	Artikkelnummer Item number	Kapasitet i brønn Capacity in well	Vekt netto/brutto Weight net/gros	Transport volum Transport volume
KBKNS-160-1 GN	07851000	1 x 1/1 GN-150 mm	57 / 72 kg	0,40 m ³
KBKNS-160-1 GN S	07851000	1 x 1/1 GN-150 mm	37 / 57 kg	0,40 m ³
KBKNS-160-2 GN	07852000	2 x 1/1 GN-150 mm	77 / 92 kg	0,66 m ³
KBKNS-160-2 GN S	07852000	2 x 1/1 GN-150 mm	57 / 77 kg	0,66 m ³
KBKNS-160-3 GN	07853000	3 x 1/1 GN-150 mm	89 / 104 kg	0,97 m ³
KBKNS-160-3 GN S	07853000	3 x 1/1 GN-150 mm	69 / 84 kg	0,97 m ³
KBKNS-160-4 GN	07854000	4 x 1/1 GN-150 mm	110 / 125 kg	1,22 m ³
KBKNS-160-4 GN S	07854000	4 x 1/1 GN-150 mm	90 / 105 kg	1,22 m ³
KBKNS-160-5 GN	07855000	5 x 1/1 GN-150 mm	132 / 144 kg	1,47 m ³
KBKNS-160-5 GN S	07855000	5 x 1/1 GN-150 mm	112 / 124 kg	1,47 m ³
KBKNS-160-6 GN	07856000	6 x 1/1 GN-150 mm	155 / 170 kg	1,75 m ³
KBKNS-160-6 GN S	07856000	6 x 1/1 GN-150 mm	135 / 150 kg	1,75 m ³

S= sentralkjøling / central cooling.

Modell Model	Mål Dimension	Avløp Drain
KBKNS-160-1 GN	400 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-1 GN S	400 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-2 GN	800 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-2 GN S	800 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-3 GN	1200 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-3 GN S	1200 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-4 GN	1525 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-4 GN S	1525 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-5 GN	1850 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-5 GN S	1850 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-6 GN	2175 x 650 x 900 mm	3/4" – DN 20
KBKNS-160-6 GN S	2175 x 650 x 900 mm	3/4" – DN 20

Modell Model	Strømart Kind of current	Kjøleeffektbehov ved sentralkjøling Power requirement central cooling
KBKNS-160-1 GN	230 V - 1 – 50 HZ – 320 W	
KBKNS-160-1 GN S	230 V - 1 – 50 HZ – 125 W	250 W /-10
KBKNS-160-2 GN	230 V - 1 – 50 HZ – 455 W	
KBKNS-160-2 GN S	230 V - 1 – 50 HZ – 125 W	400 W /-10
KBKNS-160-3 GN	230 V - 1 – 50 HZ – 455 W	
KBKNS-160-3 GN S	230 V - 1 – 50 HZ – 125 W	400 W /-10
KBKNS-160-4 GN	230 V - 1 – 50 HZ – 455 W	
KBKNS-160-4 GN S	230 V - 1 – 50 HZ – 125 W	400 W /-10
KBKNS-160-5 GN	230 V - 1 – 50 HZ – 495 W	
KBKNS-160-5 GN S	230 V - 1 – 50 HZ – 125 W	550 W /-10
KBKNS-160-6 GN	230 V - 1 – 50 HZ – 495 W	
KBKNS-160-6 GN S	230 V - 1 – 50 HZ – 125 W	550 W /-10

TD-500741 - Rev. 8. des. 2015 -GS.

Tegninger og øvrig dokumentasjon finnes på våre nettsider www.rustfriebergh.no

Sertifisert av 