

# Teknisk informasjon KBK-60

Temperatur i brønn/well 4-7 C.

Modell Model	Artikkelnummer Item number	Mål på brønn Dimension well	Vekt netto/brutto Weight net/gros	Transport volum Transport volume
KBK-60-1 GN	08201000	335 x 540 x 60 mm	42 / 62 kg	0,20 m <sup>3</sup>
KBK-60-1 GN S	08201000	335 x 540 x 60 mm	22 / 42 kg	0,20 m <sup>3</sup>
KBK-60-2 GN	08202000	660 x 540 x 60 mm	62 / 82 kg	0,42 m <sup>3</sup>
KBK-60-2 GN S	08202000	660 x 540 x 60 mm	42 / 62 kg	0,42 m <sup>3</sup>
KBK-60-3 GN	08203000	985 x 540 x 60 mm	84 / 104 kg	0,65 m <sup>3</sup>
KBK-60-3 GN S	08203000	985 x 540 x 60 mm	64 / 84 kg	0,65 m <sup>3</sup>
KBK-60-4 GN	08204000	1310 x 540 x 60 mm	106 / 126 kg	0,85 m <sup>3</sup>
KBK-60-4 GN S	08204000	1310 x 540 x 60 mm	86 / 106 kg	0,85 m <sup>3</sup>
KBK-60-5 GN	08205000	1635 x 540 x 60 mm	128 / 148 kg	1,08 m <sup>3</sup>
KBK-60-5 GN S	08205000	1635 x 540 x 60 mm	108 / 118 kg	1,08 m <sup>3</sup>
KBK-60-6 GN	08206000	1960 x 540 x 60 mm	145 / 155 kg	1,38 m <sup>3</sup>
KBK-60-6 GN S	08206000	1960 x 540 x 60 mm	125 / 135 kg	1,38 m <sup>3</sup>

S= sentralkjøling / central cooling.

Modell Model	Flensmål Dimension	Anbefalt utsparingsmål Cut out dimension	Avløp Drain
KBK-60-1 GN	427 x 630 x 12 mm	384 x 605 mm	3/4" – DN 20
KBK-60-1 GN S	427 x 630 x 12 mm	384 x 605 mm	3/4" – DN 20
KBK-60-2 GN	752 x 630 x 12 mm	709 x 605 mm	3/4" – DN 20
KBK-60-2 GN S	752 x 630 x 12 mm	709 x 605 mm	3/4" – DN 20
KBK-60-3 GN	1077 x 630 x 12 mm	1034 x 605 mm	3/4" – DN 20
KBK-60-3 GN S	1077 x 630 x 12 mm	1034 x 605 mm	3/4" – DN 20
KBK-60-4 GN	1402 x 630 x 12 mm	1359 x 605 mm	3/4" – DN 20
KBK-60-4 GN S	1402 x 630 x 12 mm	1359 x 605 mm	3/4" – DN 20
KBK-60-5 GN	1727 x 630 x 12 mm	1684 x 605 mm	3/4" – DN 20
KBK-60-5 GN S	1727 x 630 x 12 mm	1684 x 605 mm	3/4" – DN 20
KBK-60-6 GN	2052 x 630 x 12 mm	2009 x 605 mm	3/4" – DN 20
KBK-60-6 GN S	2052 x 630 x 12 mm	2009 x 605 mm	3/4" – DN 20

Modell Model	Strømart Kind of current	Kjøleeffektbehov ved sentralkjøling Power requirement central cooling
KBK-60-1 GN	230 V - 1 – 50 HZ – 320 W	
KBK-60-1 GN S	230 V - 1 – 50 HZ – 125 W	250 W /-10
KBK-60-2 GN	230 V - 1 – 50 HZ – 455 W	
KBK-60-2 GN S	230 V - 1 – 50 HZ – 125 W	400 W /-10
KBK-60-3 GN	230 V - 1 – 50 HZ – 455 W	
KBK-60-3 GN S	230 V - 1 – 50 HZ – 125 W	400 W /-10
KBK-60-4 GN	230 V - 1 – 50 HZ – 455 W	
KBK-60-4 GN S	230 V - 1 – 50 HZ – 125 W	400 W /-10
KBK-60-5 GN	230 V - 1 – 50 HZ – 495 W	
KBK-60-5 GN S	230 V - 1 – 50 HZ – 125 W	550 W /-10
KBK-60-6 GN	230 V - 1 – 50 HZ – 495 W	
KBK-60-6 GN S	230 V - 1 – 50 HZ – 125 W	550 W /-10

TD-500820 - Rev. 8. des. 2015 -GS.

Tegninger og øvrig dokumentasjon finnes på våre nettsider [www.rustfriebergh.no](http://www.rustfriebergh.no)