

Teknisk informasjon RBKP-DI

Modell Model	Artikkelnummer Item number	Vekt netto/brutto Weight net/gros	Transport volum Transport volume
RBKP-DI-1GN	07861020	40/60 kg	0,29 m ³
RBKP-DI-1GN S	07861020	20/40 kg	0,29 m ³
RBKP-DI-2GN	07862020	62 / 82 kg	0,42 m ³
RBKP-DI-2GN S	07862020	42 / 62 kg	0,42 m ³
RBKP-DI-3GN	07863020	84 / 104 kg	0,65 m ³
RBKP-DI-3GN S	07863020	64 / 84 kg	0,65 m ³
RBKP-DI-4GN	07864020	106 / 126 kg	0,85 m ³
RBKP-DI-4GN S	07864020	86 / 106 kg	0,85 m ³
RBKP-DI-5GN	07865020	128 / 148 kg	1,08 m ³
RBKP-DI-5GN S	07865020	108 / 128 kg	1,08 m ³
RBKP-DI-6GN	07866020	150 / 170 kg	1,38 m ³
RBKP-DI-6GN S	07866020	130 / 150 kg	1,38 m ³

S= sentralkjøling / central cooling.

Modell Model	Flensmål Flange dimension	Utsparingsmål Cut out dimension	Strømart Kind of current
RBKP-DI-1GN	440 x 630 mm	420 x 605 mm	230 V - 1 – 50 HZ – 140 W
RBKP-DI-1GN S	440 x 630 mm	420 x 605 mm	230 V - 1 – 50 HZ – 25 W
RBKP-DI-2GN	765 x 630 mm	745 x 605 mm	230 V - 1 – 50 HZ – 140 W
RBKP-DI-2GN S	765 x 630 mm	745 x 605 mm	230 V - 1 – 50 HZ – 25 W
RBKP-DI-3GN	1090 x 630 mm	1070 x 605 mm	230 V - 1 – 50 HZ – 140 W
RBKP-DI-3GN S	1090 x 630 mm	1070 x 605 mm	230 V - 1 – 50 HZ – 25 W
RBKP-DI-4GN	1415 x 650 mm	1395 x 605 mm	230 V - 1 – 50 HZ – 190 W
RBKP-DI-4GN S	1415 x 630 mm	1395 x 605 mm	230 V - 1 – 50 HZ – 25 W
RBKP-DI-5GN	1740 x 630 mm	1720 x 605 mm	230 V - 1 – 50 HZ – 290 W
RBKP-DI-5GN S	1740 x 630 mm	1720 x 605 mm	230 V - 1 – 50 HZ – 25 W
RBKP-DI-6GN	2065 x 630 mm	2045 x 605 mm	230 V - 1 – 50 HZ – 290 W
RBKP-DI-6GN S	2065 x 630 mm	2045 x 605 mm	230 V - 1 – 50 HZ – 25 W

Modell Model	Kuldemedie Refrigerant	Kapillarrør Capillary tube	Kjøleeffektbehov ved sentralkjøling Power requirement central cooling
RBKP-DI-1GN	R290 - 0,076 kg	Ø 0,8 – 1500 mm	
RBKP-DI-1GN S			250 W /-10
RBKP-DI-2GN	R290 - 0,076 kg	Ø 0,8 – 1500 mm	
RBKP-DI-2GN S			250 W /-10
RBKP-DI-3GN	R290 - 0,090 kg	Ø 1,0 – 3000 mm	
RBKP-DI-3GN S			250 W /-10
RBKP-DI-4GN	R290 - 0,100 kg	Ø 1,0 – 1800 mm	
RBKP-DI-4GN S			350 W /-10
RBKP-DI-5GN	R290 - 0,140 kg	Ø 0,8 – 2300 mm	
RBKP-DI-5GN S			470 W /-10
RBKP-DI-6GN	R290 - 0,140 kg	Ø 0,8 – 2000 mm	
RBKP-DI-6GN S			470 W /-10

TD-500823 - Rev. 21. feb. 2025.

Tegninger og øvrig dokumentasjon finnes på våre nettsider www.rustfriebergh.no