

Teknisk informasjon RBDM-D

RBDM-D er en serveringsdisk beregnet for å holde tilfredsstillende serveringstemperatur i en allerede nedkjølt vare.

RBDM-D er ikke beregnet for nedkjøling eller lagring av matvarer.

Temperatur i monter/display 4-7 C.

Modell Model	Artikkelnummer Item number	Mål Dimension	Vekt netto/brutto Weight net/gros	Transport volum Transport volume
RBDM-D-600	10980600	600 x 795 x 600/1350 mm	148 / 160 kg	0,95 m ³
RBDM-D-600 S	10980600	600 x 795 x 600/1350 mm	108 / 140 kg	0,95 m ³
RBDM-D-800	10980800	800 x 795 x 600/1350 mm	148 / 160 kg	1,33 m ³
RBDM-D-800 S	10980800	800 x 795 x 600/1350 mm	128 / 140 kg	1,33 m ³
RBDM-D-1000	10981000	1000 x 795 x 600/1350 mm	169 / 183 kg	1,88 m ³
RBDM-D-1000 S	10981000	1000 x 795 x 600/1350 mm	149 / 163 kg	1,88 m ³
RBDM-D-1200	10981200	1200 x 795 x 600/1350 mm	189 / 203 kg	1,98 m ³
RBDM-D-1200 S	10981200	1200 x 795 x 600/1350 mm	169 / 183 kg	1,98 m ³
RBDM-D-1600	10981600	1600 x 795 x 600/1350 mm	214 / 230 kg	2,53 m ³
RBDM-D-1600 S	10981600	1600 x 795 x 600/1350 mm	194 / 210 kg	2,53 m ³
RBDM-D-2000	10982000	2000 x 795 x 600/1350 mm	225 / 241 kg	3,13 m ³
RBDM-D-2000 S	10982000	2000 x 650 x 600/1350 mm	245 / 261 kg	3,13 m ³

S= sentralkjøling / central cooling.

Modell Model	Mål på hyller Dimension shelves	Mål topplate Dimension top plate
RBDM-D-600	500 x 620 mm	455 x 540 mm
RBDM-D-600 S	500 x 620 mm	455 x 540 mm
RBDM-D-800	700 x 620 mm	655 x 540 mm
RBDM-D-800 S	700 x 620 mm	655 x 540 mm
RBDM-D-1000	900 x 620 mm	855 x 540 mm
RBDM-D-1000 S	900 x 620 mm	855 x 540 mm
RBDM-D-1200	1100 x 620 mm	1055 x 540 mm
RBDM-D-1200 S	1100 x 620 mm	1055 x 540 mm
RBDM-D-1600	1500 x 620 mm	1455 x 540 mm
RBDM-D-1600 S	1500 x 620 mm	1455 x 540 mm
RBDM-D-2000	4 x 935 x 620 mm	1855 x 540 mm
RBDM-D-2000 S	4 x 935 x 620 mm	1855 x 540 mm

Modell Model	Strømart Kind of current	Kjøleeffektbehov ved sentralkjøling Power requirement central cooling
RBDM-D-600	230 V - 1 - 50 HZ - 450 W	
RBDM-D-600 S	230 V - 1 - 50/60 HZ - 280 W	750 W /-10
RBDM-D-800	230 V - 1 - 50 HZ - 530 W	
RBDM-D-800 S	230 V - 1 - 50/60 HZ - 300 W	750 W /-10
RBDM-D-1000	230 V - 1 - 50 HZ - 540 W	
RBDM-D-1000 S	230 V - 1 - 50/60 HZ - 310 W	750 W /-10
RBDM-D-1200	230 V - 1 - 50/HZ - 620 W	
RBDM-D-1200 S	230 V - 1 - 50/60 HZ - 310 W	750 W /-10
RBDM-D-1600	230 V - 1 - 50 HZ - 790 W	
RBDM-D-1600 S	230 V - 1 - 50/60 HZ - 360 W	850 W /-10
RBDM-D-2000	230 V - 1 - 50 HZ - 960 W	
RBDM-D-2000 S	230 V - 1 - 50/60 HZ - 390 W	850 W /-10

Modell Model	Kuldemedie Refrigerant	Kapillarrør Capillary tube	Kjøleeffektbehov ved sentralkjøling Power requirement central cooling
RBDM-D-600	R290 - 0,090 kg	Ø 1,0 – 2800 mm	
RBDM-D-600 S			470 W /-10
RBDM-D-800	R290 - 0,140 kg	Ø 0,8 – 1460 mm	
RBDM-D-800 S			470 W /-10
RBDM-D-1000	R290 - 0,140 kg	Ø 0,8 – 1460 mm	
RBDM-D-1000 S			470 W /-10
RBDM-D-1200	R290 - 0,150 kg	Ø 1,25 – 1500 mm	
RBDM-D-1200 S			640 W /-10
RBDM-D-1600	R290 - 0,150 kg	Ø 1,25 – 1800 mm	
RBDM-D-1600 S			850 W /-10
RBDM-D-2000	R290 – 0,150 kg	Ø 1,25 – 2000 mm	
RBDM-D-2000 S			950 W /-10

RBDM kan leveres med strømart 230 V – 1 – 60 HZ på forespørsel
TD-501046 - Rev. 20. jan 2025 - GS.